


ZY-RVCO-S08 溢流阀
ZY-RVCO-S08 Relief Valves

描述 DESCRIPTION:

旋入式, 筒式, 直接作用, 提升式, 通常 关闭液压安全阀。

A screw-in, cartridge style, direct acting, poppet type, normally closed hydraulic relief valve.

工作原理 OPERATION:

ZY-RVCO-S08 通常用来保护液压 压力瞬变的分量。当压力 入口(1)达到阀门设定值, 阀门开始向油箱开启 (2) 节流以使压力上升最小化。

The **ZY-RVCO-S08** typically used to protect hydraulic components from pressure transients. When the pressure at the Inlet (1) reaches the valve setting, the valve starts to open to tank (2) throttling flow to minimize the pressure rise.

特性 RATINGS:

工作压力: 350 bar

最大流量: 30 L/min

最大泄漏: 在80% 的开启压力时, 0.25 毫升/分钟 (5 滴/分钟)

温度范围: -30°C ~ 110°C

介质: 粘度介于7.4~420 cSt (50~2000 sus)的矿物油或具有润滑作用的合成油
插孔: ZY-VC08-2

Operating Pressure: 350 bar

Maximum Flow 30 L/min

Maximum Internal Leakage: 0.25 cc/minute (5 drops/minute) max. to 80% of nominal setting



Temperature: -30°C to 110°C

Fluids: Mineral-based or synthetics with lubricating properties at viscosities of 7.4 to 420 cSt (50 to 2000 sus);

Cavity: ZY-VC08-2


机能符号 SYMBOLS:

ISO:


性能图 PERFORMANCE: (Cartridge Only)


ZY-RVCO

尺寸 DIMENSIONS:



特点 FEATURES:

- 调节装置不会旋出阀体。
- 尺寸紧凑。

- Adjustments cannot be backed out of the valve.
- Compact size.

订购型号 TO ORDER:

