


ZY-CRA-04 直动式溢流阀
ZY-CRA-04 Relief, Direct-Acting Poppet

描述 DESCRIPTION:



螺纹插装、直动型、座阀式溢流阀, 适用于要求极小内泄漏的低流量液压回路。
A screw-in, cartridge-style, direct-acting, poppet-type, hydraulic relief valve intended for lower flow circuits requiring low internal leakage.

工作原理 OPERATION:

ZY-CRA-04 直动型(面差式)溢流阀反应敏捷, 压力差小, 常应用在系统压力控制。
The **ZY-CRA-04** Direct acting, differential area type, quick reaction, and small pressure gap relief valves, are used to control the pressure setting of other system.

机能符号 SYMBOLS:

ISO:


性能图 PERFORMANCE: (Cartridge Only)

特性 RATINGS:

工作压力: 310bar

额定流量: 45 L/min

温度范围: -40°C ~ 120°C

介质: 粘度介于 7.4~420 cSt (50~2000 sus) 的矿物油或具有润滑作用的合成油

阀孔: ZY-T203;


Operating Pressure: 310bar

Rated Flow : 45 L/min

Temperature: -40 to 120°C

Fluids: Mineral-based or synthetics with lubricating properties at viscosities of 7.4 to 420 cSt (50 to 2000 sus);

Cavity: ZY-T203;

尺寸 DIMENSIONS:

特点 FEATURES:

- 调节装置不会旋出阀体。
- 压力变化响应快。
- 尺寸紧凑。
- Adjustments cannot be backed out of the valve.
- Rapid response to pressure changes.
- Compact size.

订购型号 TO ORDER:
ZY-CRA-04 —
调压范围
Pressure Range

3~105bar	L
7~210bar	M
10~310bar	H

调节选件
Adjustment Option

S5内六角头 (S5 Hex Allen Head)	A
铝合金手柄 (Dia. Alum Knob)	B
盖式隐藏式 (Hiding Adj)	C

(Seals)密封材料

Buna N(Sta)
N 丁腈橡胶(标准型)
V (Fluorocarbon)氟橡胶